Crossflame[™] Silver Grill





Features/Specifications

- Two 25,000 BTU type 304 stainless steel Crossflame® burners (patented)
- Exclusive Crossflame[®] radiant system (Trademarked and Patented)
- 25,000 BTU infra-red sear burner (on select models)
- 35" Grill: 765 sq. in cooking surface (560 primary, 205 secondary)
- 41" Grill: 925 sq. in cooking surface (675 primary, 250 secondary)
- Two position, heavy gauge stainless steel welded grilling racks
- "Sure Light" ignition system
- Cooking zone dividers
- Heavy gauge warming rack
- Temperature gauge
- Control illumination with yellow LED lighting*
- 15,000 BTU rotisserie burner with smoker tray*
- Heavy duty rotis rod & forks with grill mounted stowage for rotis rod*
- Two hi-power halogen interior grilling lights*

*NOTE: features with * are specific to "R" model versions only



Patented Crossflame® burner technology



Interior view of the CGA35-2GR Ultra-even heat with the shown with rotisserie, interior and control lighting



Professional Quality seamless welded construction



Caliber patented Crossflame[®] radiant system

FOR MORE INFORMATION, VISIT OUR WEBSITE: CALIBERAPPLIANCES.COM



Expect Great Heat[™]

Clearances to Non-Combustible Construction*



Important! Gas fittings, regulator, and installer supplied shut-off valves must be easily accessible.

* NOTE: All dimensions shown refer to installation into a non-combustible enclosure. Minimum dimensions to combustible material is 12" to right, left, above, and below the grill. A minimum of 12" clearance to combustiles from the rear of the grill is required.

Build-in planning guide for non-combustible enclosures*

- 31/2" MINIMUM

CGA35 models = 30 5/8'

CGA41 models = 37"

to non-combustible constructi minimum (lid open clearance)

12" (to combustible construction)

struction

grill exhaust

Bottom of support

ų.

191 2.2.

NOTES 1. Except where noted, a solid deck is not required for product shown on this page. Product is designed to hang from the countertop. Provide minimum 6" x 6" clearance in rear corner of product cutout for gas connection. 2. Additional notch needed(L/R side) in countertop overhang to provide flush

mounting of unit to island front face. see illustration below



3. If the island is designed using a backguard apron/backsplash, locate electrical service on the left hand side for connection of the rotiserrie motor connection.

> 6"x 6" Minimum opening forgas supply and electrical supply lines.

10 square inches Minimum ventilation required for each side of the enclosure

Crossflame Silver™ Grill Models: 35" Grills 41" Grills



O

Φ

Φ

CGA35-2G-L/N:

no rotisserie burner,

No LED or control lighting

(2) grill burners,

0 • CGA41-2G-1SR-L/N: CGA35-2GR-L/N: (2) grill burners, (2) grill burners, (1) rotisserie burner, (1) sear burner, interior and control panel lighting (*shown above)

(1) rotisserie burner, interior and control panel lighting

O

000





41" Cart: 35" Cart: 2 Doors & 2 fold down 2 Doors & 2 fold down side shelves (14" width each) side shelves (14" width each) Full depth of cart 24" Full depth of cart 24" -62 1/2" full width 68 1/2" full width 413/4" w/ side shelves down 473/4" w/ side shelves down ٠ • 0 000. Φ Φ cart height 40 1/2" -34 1 36" width width 1" Minimum ground to vent bottom

Freestanding Grills on Cart (any model from above may be ordered and assembled to its corrresponding size) Grill Head and Carts require minor assembly and are shipped in separate package

CALIBERAPPLIANCES.COM

Locate 110V electrical service to the left hand side beneath grill. (2GR and 1SR models only)

12½"

31/4".

35^{1/2} Max

10 square inches

of the enclosure

Minimum ventilation

required for each side

see note 3.

above right for

for rotisserie

electrical placement

191/

see note

above right for

ounterton not

As part of our ongoing product improvement processes, Caliber Appliances reserves the right to change design, specifications, and materials without notice.

17812 Metzler Lane Huntington Beach, California 92647 714.848.1349 Office